

GATOR CONE CRUSHERS

Crusher size	Bare Crusher Weight Lbs. (Kgs.)	Blow, Blow Liner Weight Lbs. (Kgs.)	Head Main Shaft, Mantle and Feed Plate Assy Weight Lbs. (Kgs.)	Countershaft Assy Weight Lbs. (Kgs.)	Countershaft Box & Eccentric Assy Weight Lbs. (Kgs.)	Full Load Countershaft RPM	Horsepower (electric)
3' Standard	22,000 (9966)	4,000 (1812)	3,700 (1676)	2,000 (906)	1,200 (543)	580	100
3' Short Head	23,200 (10509)	4,500 (2038)	4,400 (1993)	2,000 (906)	1,200 (543)	580	100
4-1/4' Standard	49,500 (22423)	10,800 (4892)	8,000 (3624)	2,800 (1268)	2,300 (1041)	485	200
4-1/4' Short Head	49,800 (22559)	9,600 (4348)	9,500 (4303)	2,800 (1268)	2,300 (1041)	485	200
5-1/2' Standard	95,400 (43216)	22,600 (10237)	16,700 (7565)	4,700 (2129)	4,200 (1902)	485	300
5-1/2' Short Head	96,700 (43805)	20,200 (9150)	20,400 (9241)	4,700 (2129)	4,200 (1902)	485	300

- Built using "Tried and True" technology.
- Manual adjustment and locking on 3'.
- Hydraulic locking and adjustment on 4-1/4' and larger.
- Long life and low operating and maintenance cost built into every crusher.
- Customer service, before, during and after the sale.
- Off the shelf parts for customer convenience.

Please contact your local Gator dealer or Gator Machinery Co. direct for more information.

